

TORQUE TESTER DI-4B-25

The best for daily Torque check of a small impact tool, an air driver, and a high output electric driver

The feature of DI-4B-25

- Measurement is possible up to a maximum of 25 N-m.
- It is the number counter of blows for impact tools.
- Measurement in the state where the socket was attached is possible.



The main functions

High luminosity LED display

LED is adopted as a display part.
A numerical value can be read clearly also in a dark place.

Battery drive

It can be used being unable to choose a place and convenient for carrying by the spot.
An exclusive charger is attached.



Auto-power-off

A power source is automatically turned off after neglect for 5 minutes.

Display zero clearance

The zero clearance of the measurements is automatically carried out in setting time.
(A setup in 0.5 - 3 seconds is possible)

Specification

Model name	DI-4B-25		
Measuring range (at the time of Track)	0.30~25 N·m 3.0~250 kgf·cm 3.0~220 lbf·in		
Accuracy	±0.5% (or less 499±3digit)		
The display method	4 figures LED display		
The measurement direction	CW-CCW (right and left) It is selection measurement by the change switch.		
Mode	Track, Peak, Peak-Down (Operation is 70digit or more)		
Auto clear time	In 0.5 - 3.0 seconds (0.5-second interval, an indication is automatically given zero.) It is a manual zero clearance by 0.0-second setup		
Blow measurement range	Zero to 99 blow		
Blow Measurement time	0.1 - 9.9 seconds		
Data output	ASCII format (baud rate 19200)		
Appearance	Dimension: 150(W) x220(D) x74 (H) Weight: About 2.1kg		
Power supply	nickel-cadmium battery 1.2v 5 cells (700mAh) Auto power OFF (after [OFF] the neglect during 5 minutes)		
Charge time / use time	At the time of charge 6 hour /, and the maximum charge Continuation about 8-hour use	Hard joint 17mm of hexagon-head-bolt opposite neighborhoods Rotate about 1-/10 by the time a nut or a bolt arrives at a bearing surface and reaches all torque. For rigid object.	
The contents of a set (one piece each)	Hard joint (M10) / Soft joint (M10) / 9.5 sq. drive Socket (Hexagon head socket 17)		
	6.35Hex bit (Hexagon head socket 17)		
	Receipt case		
	AC/DC adaptor (Please choose from 120V and 230V.)		
	Inspection-report / proofreading certificate /Traceability system figure		

Please check the newest information and the details of each product in a homepage. 《URL <http://www.cedar.co.jp>》

	  	SUGISAKI METER CO.,LTD. URL http://www.cedar.co.jp E-mail sales@cedar.co.jp
--	--	--

The contents of a catalog may change specification and a design without a preliminary announcement.